



H3.0XT

DISTINGUISHING MARKS	1.1	Manufacturer	
	1.2	Manufacturer's type designation	
		Engine / transmission	
		Brake Type	
	1.3	Drive: electric (battery or mains), diesel, petrol, LPG	
	1.4	Operator type: hand, pedestrian, standing, seated, order-picker	
	1.5	Rated capacity / rated load	Q (t)
	1.6	Load centre distance	c (mm)
	1.8	Load distance, centre of drive axle to fork (1)	x (mm)
1.9	Wheelbase	y (mm)	

HYSTER	
H3.0XT	
Yanmar 2.6L Basic Powershift 1-speed Drum Brakes	
Diesel	
Seat	
	3.0
	500
	478
	1700

WEIGHTS	2.1	Service weight	kg
	2.2	Axle loading, laden front / rear	kg
	2.3	Axle loading, unladen front / rear	kg

4690	
6586	1087
1892	2798

TYRES & CHASSIS	3.1	Tyres: L = Pneumatic, V = sSolid, SE = Pneumatic Shape Solid	
	3.2	Tyre size, front	
	3.3	Tyre size, rear	
	3.5	Number of wheels, front/rear (x = driven)	
	3.6	Tread, front	b ₁₀ (mm)
	3.7	Tread, rear	b ₁₁ (mm)

SE	
28 x 9 - 15	
6.50 x 10	
2x	2
	970
	993

DIMENSIONS	4.1	Tilt of mast / fork carriage forward / backward	α / β (°)
	4.2	Height, mast lowered	h ₁ (mm)
	4.3	Free lift □	h ₂ (mm)
	4.4	Lift □	h ₃ (mm)
	4.5	Height, mast extended ◆	h ₄ (mm)
	4.7	Height of overhead guard (High/Intermediate) ■	h ₆ (mm)
	4.7.1	Height of cabin (High/Intermediate) ■	h ₆ (mm)
	4.8	Seat height relating to SIP/stand height ◆	h ₇ (mm)
	4.12	Coupling height	h ₁₀ (mm)
	4.19	Overall length	l ₁ (mm)
	4.20	Length to face of forks	l ₂ (mm)
	4.21	Overall width	b ₁ /b ₂ (mm)
	4.22	Fork dimensions DIN ISO 2331	s/e/l (mm)
	4.23	Fork carriage ISO 2328, class/type A, B	
	4.24	Fork carriage width ●	b ₃ (mm)
	4.31	Ground clearance, laden, below mast	m ₁ (mm)
	4.32	Ground clearance, centre of wheelbase	m ₂ (mm)
4.34.1	Aisle width for pallets 1000 x 1200 crossways	A _{st} (mm)	
4.34.2	Aisle width for pallets 800 x 1200 lengthways	A _{st} (mm)	
4.35	Turning radius	W ₆ (mm)	
4.36	Internal turning radius	b ₁₃ (mm)	
4.43	Step height	(mm)	

	6	6
	2195	
	150	
	3105	
	4335	
	2250	2210
	2258	2218
	1149	
	369	
	3696	
	2696	
	1206	
	50x125x1000	
	IIIA	
	1067	
	100	
	210	
	3802	
	4002	
	2324	
	618	
	435	

PERFORMANCE DATA	5.1	Travel speed, laden/unladen	km/h
	5.2	Lift speed, laden/unladen	m/sec
	5.3	Lowering speed, laden/unladen	m/sec
	5.5	Drawbar pull, laden/unladen *	kN
	5.7	Gradeability, laden/unladen †	%
	5.9	Acceleration time, laden/unladen	seconds
	5.10	Service brake	

	18.7	18.9
	0.58	0.61
	0.58	0.50
	13.4	13.8
	12.3	30.5
	5.3	4.5
	Hydraulic	

PERFORMANCE DATA	7.1	Engine manufacturer/type	
	7.2	Engine power according to ISO 1585 / DIN 6271	kW
	7.3	Rated speed	rpm
	7.4	Number of cylinders/displacement	(-)/cm ³
	7.5	Fuel consumption according to VDI cycle	l/h (DSL) or kg/h (LPG)

Yanmar 2.6L	
33.0	
2350	
4	2659
3.5	

DRIVE/LIFT MECHANISM	8.1	Type of drive unit	
-----------------------------	-----	--------------------	--

Automatic	
-----------	--

ADDITIONAL DATA	10.1	Operating pressure for attachments	bar
	10.2	Oil volume for attachments	l/min
	10.3	Hydraulic oil tank, capacity	litres
	10.4	Fuel tank, capacity	liters (DSL) or kg (LPG)
	10.7	Sound pressure level at the driver's seat ◇	dB(A)
	10.7.1	Guaranteed sound power 2000/14/EC	dB(A)
	10.8	Towing coupling type / DIN type	

	0-155
	60
	42
	69
	79
	104
	Pin

NOTE:

Specifications are affected by the condition of the vehicle and how it is equipped, as well as the nature and condition of the operating area. If these specifications are critical, the proposed application should be discussed with your dealer.

- Top of forks
- ◆ Without load backrest
- h₆ subject to +/- 10 mm tolerance
- ◇ Full-suspension seat in depressed position
- Add 32mm with load backrest
- ◆ Stacking aisle width (lines 4.34.1 & 4.34.2) are based on the VDI standard calculation as shown on illustration. The British Industrial Truck Association recommends the addition of 100 mm to the total clearance (dimension a) for extra operating margin at the rear of the truck.
- * @ 1.6km/h. Drawbar pull performance figure (line 5.4) is only indicative for comparison purpose. These performances are only possible for a short period of time.
- † @ 4.8km/h. Gradeability figures are provided for comparison of tractive performance, but are not intended to endorse the operation of the vehicle on the stated inclines. Follow instructions in the operating manual regarding operation on inclines.
- ◇ L_{PAZ}, Measured according to the test cycles and based on the weighting values contained in EN12053

MAST TABLES:

- ✳ With load backrest
- Without load backrest

NOTICE:

Care must be exercised when handling elevated loads. When the carriage and/or load is elevated, truck stability is reduced. It is important that the mast tilt in either direction is kept to a minimum when loads are elevated. Operators must be trained and must read, understand and follow the instructions contained in the Operating Manual.

All values are nominal values and they are subject to tolerances. For further information, please contact the manufacturer. Hyster products are subject to change without notice.

Forklift trucks illustrated may feature optional equipment.

Values may vary with alternative configurations.

CE Safety:


This truck conforms to the current EU requirements.

Specification data is based on VDI 2198

EQUIPMENT AND WEIGHT:

Weights (lines 2.1, 2.2, 2.3) are based on the following specifications:
Complete truck with 3292mm (H2.0-2.5XT) / 3209mm (H3.0XT) TOF 2 stage LFL mast, standard carriage and 1 000 mm forks with manual hydraulics, overhead guard and pneumatic shaped solid drive and steer tyres.

TRUCK DIMENSIONS




$$A_{st} = W_b + x + l_6 + a \text{ (see lines 4.34.1 \& 4.34.2)}$$

a = minimum operating clearance


(VDI standard = 200 BITA recommendation = 300mm)

l_6 = Load length



RATED CAPACITIES

Standard carriage



Standard 500mm load centre


Load centre

Distance from front of forks to centre of gravity of load.

Rated load

Based on vertical masts up to 3 292 mm.

Integral side shift carriage with fork positioner



Standard 500mm load centre

Load centre

Distance from front of forks to centre of gravity of load.

Rated load

Based on vertical masts up to 3 292 mm.



MAST AND CAPACITY INFORMATION

Values shown are for standard equipment. When using non-standard equipment, these values may change.

MASTS H3.0XT

Mast	Maximum fork height (mm)	Back tilt	Overall lowered height (mm)	Overall Extended height (mm) ✖	Free lift (top of forks) (mm) □
2-Stage Limited Free Lift	3105	6°	2195	4335	150
	3205	6°	2245	4435	150
	3605	6°	2445	4835	150
	4105	6°	2795	5335	150
	4605	6°	3045	5835	150
3-Stage Full Free Lift	4015	6°	1995	5245	1315
	4615	6°	2195	5845	1515
	4765	6°	2245	5995	1615
	4915	6°	2345	6145	1665
	5215	6°	2445	6445	1765
	5815	6°	2695	7045	2015

H2.0-3.0XT – Capacity Chart in kg @ 500mm Load Centre

MAST	Pneumatic Shaped Solid Tyres							
	Maximum fork height (mm)	Without Sideshift		With ISS & FP		Maximum Fork Height (mm)	Without Sideshift	With ISS & FP
		H2.0XT	H2.5XT	H2.0XT	H2.5XT		H3.0XT	H3.0XT
2-Stage Limited Free Lift	-	-	-	-	-	3105	2940	2900
	3290	2000	2490	1940	2420	3210	2940	2890
	3790	2000	2490	1930	2410	3605	2940	2890
	4330	2000	2490	1920	2400	4105	2940	2870
	4830	1900	2390	1820	2290	4605	2850	2760
3-Stage Full Free Lift	4350	2000	2490	1910	2390	4015	2940	2860
	4800	1910	2400	1820	2290	4615	2830	2740
	4950	1880	2370	1790	2260	4770	2790	2700
	5100	1850	2290	1760	2220	4915	2760	2660
	5550	1740	1850	1660	1860	5215	2690	2590
	6000	1560	1510	1550	1500	5815	2470	2430

H2.0-3.0XT – Capacity Chart in kg @ 600mm Load Centre

MAST	Pneumatic Shaped Solid Tyres							
	Maximum fork height (mm)	Without Sideshift		With ISS & FP		Maximum Fork Height (mm)	Without Sideshift	With ISS & FP
		H2.0XT	H2.5XT	H2.0XT	H2.5XT		H3.0XT	H3.0XT
2-Stage Limited Free Lift	-	-	-	-	-	3105	2760	2640
	3290	1840	2290	1770	2200	3210	2750	2640
	3790	1830	2280	1760	2190	3605	2750	2630
	4330	1820	2270	1740	2180	4105	2730	2610
	4830	1720	2170	1650	2080	4605	2630	2510
3-Stage Full Free Lift	4350	1820	2270	1730	2170	4015	2730	2600
	4800	1730	2180	1660	2090	4615	2610	2490
	4950	1710	2150	1630	2060	4770	2570	2460
	5100	1670	2110	1600	2020	4915	2540	2430
	5550	1580	1850	1510	1860	5215	2470	2360
	6000	1480	1510	1410	1500	5815	2320	2210

H2.0-3.0XT – Capacity Chart in kg @ 700mm Load Centre

MAST	Pneumatic Shaped Solid Tyres							
	Maximum fork height (mm)	Without Sideshift		With ISS & FP		Maximum Fork Height (mm)	Without Sideshift	With ISS & FP
		H2.0XT	H2.5XT	H2.0XT	H2.5XT		H3.0XT	H3.0XT
2-Stage Limited Free Lift	-	-	-	-	-	3105	2520	2420
	3290	1680	2100	1620	2020	3210	2520	2420
	3790	1670	2090	1610	2010	3605	2510	2410
	4330	1660	2080	1600	2000	4105	2500	2400
	4830	1580	1980	1520	1910	4605	2400	2310
3-Stage Full Free Lift	4350	1660	2080	1590	1990	4015	2500	2390
	4800	1590	1990	1520	1910	4615	2390	2290
	4950	1560	1960	1490	1880	4770	2360	2260
	5100	1530	1930	1470	1850	4915	2330	2230
	5550	1440	1840	1380	1760	5215	2260	2170
	6000	1350	1510	1290	1500	5815	2120	2030

NOTE: To calculate truck capacities with alternative truck specifications to the ones shown in the above tables, please use the Hy-Rater software.